



## Blind Rivet Nuts - Knurled body - Flange head

Materials/Finishes:  
 Steel/Zinc & yellow  
 Stainless steel/Self colour (non-preferred)  
 Aluminium/Self colour (non-preferred)



**FLG SHORT/OESTKG/{Length}**  
**FLG MED/OESTKG//{Length}**

Thread	L mm	e mm	r mm (approx.)	Hole size mm	D mm	B mm	s mm
M3	10.0	0.5-3.0	-	5.0	4.9	7.0	0.9
M4 short	10.0	0.3-3.0	7.5	6.0	5	9.0	1.0
M4 medium	11.5	3.1-4.0					
M5 short	12.0	0.3-3.0	8.5	7.0	6.9	10.0	1.0
M5 medium	15.0	3.1-4.0					
M6 short	14.5	0.5-3.0	9	9.0	8.9	12.0	1.5
M6 medium	16.0	3.1-4.5					
M8 short	16.0	0.5-3.0	11.5	11.0	10.9	15.0	1.5
M8 medium	18.5	3.1-5.5					
M10 short	17.0	0.5-3.0	-	12.0	11.9	16.0	2.0
M10 medium	22.0	3.0-6.0					
M12	23.0	1.0-4.0	-	16.0	15.9	22.0	2.0

Longer Grip-Serts are available on request